



# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/16/2016

Supersedes:11/04/2014

Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : METAL POLISH TUBE 3.5 OZ.  
Product code : 100-12

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Tarnish Remover

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 4 H227  
Skin Irrit. 2 H315  
Eye Dam. 1 H318  
Skin Sens. 1 H317

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H227 - Combustible liquid  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage

Precautionary statements (GHS-US) :

P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P261 - Avoid breathing dust, fume, gas, mist, vapor spray  
P264 - Wash affected areas thoroughly after handling  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P302+P352 - If on skin: Wash with plenty of soap and water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a poison center, doctor, physician  
P321 - Specific treatment: See section 4.1 on SDS  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P363 - Wash contaminated clothing before reuse  
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
P403+P235 - Store in a well-ventilated place. Keep cool  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification

: None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

| Name   | Product identifier  | %       | GHS-US classification                           |
|--|---------------------|---------|---|
| Water  | (CAS No) 7732-18-5  | 30 - 50 | Not classified                                  |
| Aluminium Oxide, Activated                                 | (CAS No) 1344-28-1  | 10 - 30 | Not classified                                  |
| Distillates (Petroleum), Hydrotreated Light                | (CAS No) 64742-47-8 | 10 - 30 | Asp. Tox. 1, H304                               |
| Oleic Acid   | (CAS No) 112-80-1   | 5 - 10  | Not classified                                  |
| Ammonium Hydroxide, Aqueous Solution, Conc=25%             | (CAS No) 1336-21-6  | 1 - 5   | Skin Corr. 1B, H314<br>Aquatic Acute 1, H400    |
| Silicone   | (CAS No) 63148-62-9 | 1 - 5   | Not classified                                  |
| Barium Sulfate   | (CAS No) 7727-43-7  | 1 - 5   | Not classified                                  |
| Alcohols, C12-13, Ethoxylated                              | (CAS No) 66455-14-9 | 1 - 5   | Not classified                                  |
| CI 77007   | (CAS No) 57455-37-5 | < 1     | Not classified                                  |
| 2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol | (CAS No) 4719-04-4  | < 1     | Acute Tox. 4 (Oral), H302<br>Skin Sens. 1, H317 |

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs:
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : If you feel unwell, seek medical advice.
- Symptoms/injuries after inhalation : May cause an allergic skin reaction.
- Symptoms/injuries after skin contact : Itching. Red skin. Skin rash/inflammation. Causes skin irritation.
- Symptoms/injuries after eye contact : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye damage.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. May be harmful if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Gloves.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers. Dam up the liquid spill. Plug the leak, cut off the supply.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Avoid breathing dust, fume, gas, mist, vapor spray.

Hygiene measures : Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Distillates (Petroleum), Hydrotreated Light (64742-47-8)   |                                |  |
|--|--------------------------------|--|
| USA ACGIH  | ACGIH TWA (ppm)                | 200 ppm 8 Hours  |
| Aluminium Oxide, Activated (1344-28-1)                     |                                |  |
| USA ACGIH  | ACGIH TWA (mg/m <sup>3</sup> ) | 1 mg/m <sup>3</sup> (Aluminium, insoluble compounds; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)  |
| Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6) |                                |  |
| USA ACGIH  | ACGIH TWA (ppm)                | 24 ppm   |
| USA ACGIH  | ACGIH STEL (ppm)               | 35 ppm   |
| USA OSHA   | OSHA PEL (TWA) (ppm)           | 50 ppm   |
| Barium Sulfate (7727-43-7)                                 |                                |  |
| USA ACGIH  | ACGIH TWA (mg/m <sup>3</sup> ) | 5 mg/m <sup>3</sup> (Barium sulfate; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica) |

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Safety glasses. Gloves. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                            |   |
|----------------------------|---|
| Skin and body protection   | : Wear suitable protective clothing.            |
| Respiratory protection     | : Wear appropriate mask.                        |
| Consumer exposure controls | : Avoid contact during pregnancy/while nursing. |
| Other information          | : Do not eat, drink or smoke during use.        |

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|   |                            |
|---|----------------------------|
| Physical state                              | : Liquid                   |
| Appearance                                  | : Cream . Liquid Paste.    |
| Color                                       | : Blue.                    |
| Odor  | : Ammoniacal.              |
| Odor threshold                              | : No data available        |
| pH  | : 10.5                     |
| Relative evaporation rate (butyl acetate=1) | : No data available        |
| Melting point                               | : No data available        |
| Freezing point                              | : No data available        |
| Boiling point                               | : > 100 °C                 |
| Flash point                                 | : 69 °C                    |
| Auto-ignition temperature                   | : No data available        |
| Decomposition temperature                   | : No data available        |
| Flammability (solid, gas)                   | : No data available        |
| Vapor pressure                              | : No data available        |
| Relative vapor density at 20 °C             | : No data available        |
| Relative density                            | : No data available        |
| Solubility                                  | : Poorly soluble in water. |
| Log Pow                                     | : No data available        |
| Log Kow                                     | : No data available        |
| Viscosity, kinematic                        | : No data available        |
| Viscosity, dynamic                          | : No data available        |
| Explosive properties                        | : No data available        |
| Oxidizing properties                        | : No data available        |
| Explosion limits                            | : No data available        |

#### 9.2. Other information

|             |         |
|-------------|---------|
| VOC content | : < 1 % |
|-------------|---------|

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

|                |                  |
|----------------|------------------|
| Acute toxicity | : Not classified |
|----------------|------------------|

| Alcohols, C12-13, Ethoxylated (66455-14-9) |                       |
|--|-----------------------|
| LD50 oral rat                              | > 2000 mg/kg (Rat)    |
| LD50 dermal rabbit                         | > 2000 mg/kg (Rabbit) |

# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>               |  |
|---|--|
| LD50 oral rat   | > 5000 mg/kg body weight   |
| LD50 dermal rabbit  | > 2000 mg/kg   |
| LC50 inhalation rat (mg/l)  | > 5.28 mg/l/4h Based on lack of mortality and systemic effects                         |
| <b>Aluminium Oxide, Activated (1344-28-1)</b>                                 |  |
| LD50 oral rat   | > 10000 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value) |
| <b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b> |  |
| LD50 oral rat   | 763 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)                     |
| LD50 dermal rat   | > 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)    |
| LC50 inhalation rat (mg/l)  | 0.371 mg/l/4h (Rat; Experimental value)  |
| <b>Oleic Acid (112-80-1)</b>  |  |
| LD50 oral rat   | > 19200 mg/kg (Rat)  |
| <b>Barium Sulfate (7727-43-7)</b>   |  |
| LD50 oral rat   | > 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)                  |

|   |  |
|---|--|
| Skin corrosion/irritation                           | : Causes skin irritation.<br>pH: 10.5  |
| Serious eye damage/irritation                       | : Causes serious eye damage.<br>pH: 10.5   |
| Respiratory or skin sensitization                   | : May cause an allergic skin reaction.   |
| Germ cell mutagenicity                              | : Not classified Based on available data, the classification criteria are not met  |
| Carcinogenicity                                     | : Not classified   |
| Reproductive toxicity                               | : Not classified   |
| Specific target organ toxicity (single exposure)    | : Not classified   |
| Specific target organ toxicity (repeated exposure)  | : Not classified   |
| Aspiration hazard                                   | : Not classified   |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met.  |
| Symptoms/injuries after inhalation                  | : May cause an allergic skin reaction.   |
| Symptoms/injuries after skin contact                | : Itching. Red skin. Skin rash/inflammation. Causes skin irritation.   |
| Symptoms/injuries after eye contact                 | : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye damage. |
| Symptoms/injuries after ingestion                   | : May be fatal if swallowed and enters airways. May be harmful if swallowed and enters airways.                              |

## SECTION 12: Ecological information

### 12.1. Toxicity

| <b>Aluminium Oxide, Activated (1344-28-1)</b>                                 |   |
|---|---|
| LC50 fish 1   | > 50 mg/l (NOEC; 96 h; <i>Lepomis cyanellus</i> ; Static system; Fresh water)   |
| EC50 Daphnia 1  | 1.4 mg/l (EC50; OECD 202: <i>Daphnia</i> sp. Acute Immobilisation Test; 48 h; <i>Daphnia magna</i> ; Static system; Fresh water; Experimental value)        |
| EC50 Daphnia 2  | 0.34 - 1.02 mg/l (NOEC; US EPA; 6 days; <i>Ceriodaphnia dubia</i> ; Semi-static system; Fresh water; Read-across)   |
| Threshold limit algae 1   | >= 0.052 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; <i>Pseudokirchneriella subcapitata</i> ; Static system; Fresh water; Experimental value) |
| Threshold limit algae 2   | > 45.7 mg/l (NOEC; Other; 96 h; <i>Lemna minor</i> ; Static system; Fresh water; Read-across)   |
| <b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b> |   |
| LC50 fish 1   | 16.07 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; <i>Brachydanio rerio</i> ; Static system; Fresh water; Experimental value)                     |
| EC50 Daphnia 1  | 11.9 mg/l (EC50; OECD 202: <i>Daphnia</i> sp. Acute Immobilisation Test; 48 h; <i>Daphnia magna</i> ; Static system; Fresh water; Experimental value)       |
| EC50 Daphnia 2  | 8.75 mg/l (EC0; OECD 202: <i>Daphnia</i> sp. Acute Immobilisation Test; 48 h; <i>Daphnia magna</i> ; Static system; Fresh water; Experimental value)        |
| Threshold limit algae 1   | 6.66 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; <i>Desmodesmus subspicatus</i> ; Static system; Fresh water; Experimental value)             |
| Threshold limit algae 2   | 1.56 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; <i>Desmodesmus subspicatus</i> ; Static system; Fresh water; Experimental value)             |
| <b>Oleic Acid (112-80-1)</b>  |   |
| LC50 fish 2   | 205 mg/l (LC50; 96 h; <i>Pimephales promelas</i> )  |

# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Barium Sulfate (7727-43-7)</b> |   |
|-----------------------------------|---|
| EC50 Daphnia 1                    | 32 mg/l (EC50; 48 h)  |
| Threshold limit algae 1           | ≥1.92,NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value |

### 12.2. Persistence and degradability

| <b>METAL POLISH TUBE 3.5 OZ.</b> |                  |
|----------------------------------|------------------|
| Persistence and degradability    | Not established. |

| <b>Water (7732-18-5)</b>      |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

| <b>Alcohols, C12-13, Ethoxylated (66455-14-9)</b> |   |
|---|---|
| Persistence and degradability                     | Readily biodegradable in water. Biodegradability in soil: no data available. No (test)data on mobility of the components available. |

| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |                  |
|---|------------------|
| Persistence and degradability                                   | Not established. |

| <b>CI 77007 (57455-37-5)</b>  |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

| <b>Aluminium Oxide, Activated (1344-28-1)</b> |   |
|---|---|
| Persistence and degradability                 | Biodegradability: not applicable. No (test)data on mobility of the substance available. |
| ThOD  | Not applicable  |

| <b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b> |                                 |
|---|---------------------------------|
| Persistence and degradability   | Readily biodegradable in water. |

| <b>Silicone (63148-62-9)</b>  |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

| <b>Oleic Acid (112-80-1)</b>  |  |
|-------------------------------|--|
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil. Photodegradation in the air. |
| Chemical oxygen demand (COD)  | 2.25 g O <sub>2</sub> /g substance   |
| ThOD                          | 2.89 g O <sub>2</sub> /g substance   |
| BOD (% of ThOD)               | > 0.5 (5 days; Literature study)   |

| <b>Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)</b> |  |
|---|--|
| Persistence and degradability                                     | Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the components available. Ozonation in the air. Not established. |

| <b>Barium Sulfate (7727-43-7)</b> |  |
|-----------------------------------|--|
| Persistence and degradability     | Biodegradability: not applicable. No (test)data on mobility of the substance available. Not established. |
| Biochemical oxygen demand (BOD)   | Not applicable   |
| Chemical oxygen demand (COD)      | Not applicable   |
| ThOD                              | Not applicable   |

### 12.3. Bioaccumulative potential

| <b>METAL POLISH TUBE 3.5 OZ.</b> |                  |
|----------------------------------|------------------|
| Bioaccumulative potential        | Not established. |

| <b>Water (7732-18-5)</b>  |                  |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

| <b>Alcohols, C12-13, Ethoxylated (66455-14-9)</b> |                      |
|---|----------------------|
| Log Pow   | 3.0                  |
| Bioaccumulative potential                         | Not bioaccumulative. |

| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |                  |
|---|------------------|
| Bioaccumulative potential                                       | Not established. |

| <b>CI 77007 (57455-37-5)</b> |                  |
|------------------------------|------------------|
| Bioaccumulative potential    | Not established. |

| <b>Aluminium Oxide, Activated (1344-28-1)</b> |                                    |
|---|------------------------------------|
| Bioaccumulative potential                     | No bioaccumulation data available. |

| <b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b> |  |
|---|--|
| Log Pow   | -4.67 (Calculated)                               |
| Bioaccumulative potential   | Low potential for bioaccumulation (Log Kow < 4). |

# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |   |
|---|---|
| <b>Silicone (63148-62-9)</b>                                      |   |
| Bioaccumulative potential   | Not established.  |
| <b>Oleic Acid (112-80-1)</b>                                      |   |
| Log Pow   | 5.24 - 7.18 (QSAR)  |
| Bioaccumulative potential   | Not established.  |
| <b>Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)</b> |   |
| Bioaccumulative potential   | Not bioaccumulative. Not established.                           |
| <b>Barium Sulfate (7727-43-7)</b>                                 |   |
| BCF fish 1  | 68.4 (BCF; Lepomis macrochirus)                                 |
| Bioaccumulative potential   | Low potential for bioaccumulation (BCF < 500). Not established. |

### 12.4. Mobility in soil

|   |  |
|---|--|
| <b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b> |  |
| Log Koc   | log Koc,PCKOCWIN v1.66; 1; Calculated value; Koc; PCKOCWIN v1.66; 10; Calculated value |
| <b>Oleic Acid (112-80-1)</b>  |  |
| Surface tension   | 0.033 N/m (20 °C)  |

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): NA1993, Combustible liquid, n.o.s. (Petroleum Distillates), 3, III, Limited Quantity

ICAO/IATA (air): Not Regulated,

IMO/IMDG (water): Not Regulated,

Special Provisions: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672)  
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Combustible liquid, n.o.s. (Petroleum Distillates)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name

Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672)  
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L  
CFR 175.75)

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### METAL POLISH TUBE 3.5 OZ.

|                                     |   |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard<br>Immediate (acute) health hazard<br>Fire hazard |
|-------------------------------------|---|

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                                     |  |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
|-------------------------------------|--|

#### Oleic Acid (112-80-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### METAL POLISH TUBE 3.5 OZ.

|                      |   |
|----------------------|---|
| WHMIS Classification | Class B Division 3 - Combustible Liquid |
|----------------------|---|

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

|                      |   |
|----------------------|---|
| WHMIS Classification | Uncontrolled product according to WHMIS classification criteria |
|----------------------|---|

#### Oleic Acid (112-80-1)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

#### Oleic Acid (112-80-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

N; R51/53

Full text of R-phrases: see section 16

### 15.2.2. National regulations

#### Oleic Acid (112-80-1)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on the Korean ECL (Existing Chemicals List)

### 15.3. US State regulations

#### METAL POLISH TUBE 3.5 OZ.

|   |    |
|---|----|
| U.S. - California - Proposition 65 - Carcinogens List               | No |
| U.S. - California - Proposition 65 - Developmental Toxicity         | No |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No |
| U.S. - California - Proposition 65 - Reproductive                   | No |



# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>METAL POLISH TUBE 3.5 OZ.</b>   |   |   |   |                                   |
|--|---|---|---|-----------------------------------|
| Toxicity - Male  |   |   |   |                                   |
| State or local regulations   |   | U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL) |   |                                   |
| <b>Water (7732-18-5)</b>   |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                        | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female       | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |
| <b>Alcohols, C12-13, Ethoxylated (66455-14-9)</b>                            |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                        | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female       | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |
| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>              |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                        | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female       | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |
| <b>CI 77007 (57455-37-5)</b>   |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                        | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female       | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |
| <b>Aluminium Oxide, Activated (1344-28-1)</b>                                |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                        | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female       | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |
| <b>2,2',2''-(Hexahydro-1,3,5-Triazol-1,3,5-Triyl) Triethanol (4719-04-4)</b> |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                        | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female       | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |
| <b>Silicone (63148-62-9)</b>   |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                        | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female       | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |
| <b>Oleic Acid (112-80-1)</b>   |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                        | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female       | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |
| <b>Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)</b>            |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List                        | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female       | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |

# METAL POLISH TUBE 3.5 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Barium Sulfate (7727-43-7)                            |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No  | No  |                                   |

### SECTION 16: Other information

Indication of changes : Revision - See : \*

Other information : None.


Full text of H-phrases:

|      |  |
|------|--|
| H227 | Combustible liquid                           |
| H302 | Harmful if swallowed                         |
| H304 | May be fatal if swallowed and enters airways |
| H314 | Causes severe skin burns and eye damage      |
| H315 | Causes skin irritation                       |
| H317 | May cause an allergic skin reaction          |
| H318 | Causes serious eye damage                    |
| H400 | Very toxic to aquatic life                   |

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 2 Moderate Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*